

Design. Uniqueness. Innovations



Shan IP outdoor panel provides convenient premises access for a large number of people. Assign unique key code combinations or MIFARE IC proximity cards to the panel's internal memory. Thus, users will be able to safely open the door using a unique wireless key or code.

**CAMERA** 1/3" CMOS, HD resolution

**BACKLIGHT** White LED, up to 1.5 m

**SCREEN TYPE** 4.3" color TFT

VIEWING ANGLE 150°

**SCREEN RESOLUTION** 480×272 pixels

**BODY STRUCTURE** Aluminum + acrylic glass

**PROTECTION CLASS** IP65

**DIMENSIONS** 116×210×35 mm

**COLOR** Black+silver

**POWER** 12-15 V from external power

supply or POE

**CONSUMPTION** Up to 5 W

**LOCK TYPE** Mechanical or magnetic,

up to 2 A current

**BUTTONS** Capacitive touch screen

**INSTALLATION TYPE** Surface mount

**TEMPERATURE RANGE** -40 ... +50 °C

**ACCESS CONTROL** MIFARE IC cards, user codes

## **Unique features**



## **Access control**

Use Mifare IC wireless cards or key code to unlock the door



## Touch screen

Convinient operation using capacitive touch screen



Viewing angle 150°



**POE support**No need to use additional power

cable



Product page