



Outdoor panel with touchless call button

ML-20HD

The ML-20HD outdoor panel can be used as a source of video signal for digital video recorders (DVR's), because it has separate wire for powering the outdoor panel camera in standby mode. It helps you to create ultimate video monitoring system without additional cost.

CAMERA RESOLUTION	2MP / 1MP / 960TVL	POWER	12 V from the indoor monitor
TYPE OF SIGNAL	AHD or CVBS (PAL)	CONSUMPTION	Up to 2 W
NIGHT BACKLIGHT	IR LED, up to 1.5 m	LOCK TYPE	Mechanical, up to 1 A current
SENSOR TYPE	1/2.9" CMOS	CALL BUTTON	Mechanical, with backlight
VIEWING ANGLE	115°	INSTALLATION TYPE	Surface or flush mount
MIN. ILLUMINATION	0,01 Lux	COLORS	Silver+black, gold+black
BODY STRUCTURE	Metal alloy + acrylic glass	TEMPERATURE RANGE	-40 ... +50 °C
PROTECTION CLASS	IP65	ADDITIONAL FUNCTIONS	Mechanical IR-cut filter
DIMENSIONS	45×130×24 mm		

Unique features



Operating temperature
-40 – +50 °C



Call button backlight
LED button backlight in standby mode



Viewing angle
115°



Camera mode switch
Switch the camera mode between AHD and CVBS



Product page