



Outdoor panel

ML-30CRHD


ML-30CR outdoor panel provides convenient premises access for a large number of people. Assign up to 200 unique 4-digit combinations and up to 200 MIFARE proximity cards to the panel's internal memory. Thus, immediately 400 people will be able to safely open the door using a unique wireless key or code.

CAMERA RESOLUTION	2MP / 1MP / 960TVL AHD	POWER	12 V from power supply
TYPE OF SIGNAL	or CVBS (PAL)	CONSUMPTION	Up to 4 W
NIGHT BACKLIGHT	IR LED, up to 1.5 m	LOCK TYPE	Mechanical or magnetic, up to 1 A current
SENSOR TYPE	1/3" CMOS	BUTTONS	Sensor, with backlight
VIEWING ANGLE	115°	COLORS	Black+silver, white+silver
MIN. ILLUMINATION	0,01 Lux	TEMPERATURE RANGE	-40 ... +50 °C
BODY STRUCTURE	Metal alloy + acrylic glass	ACCESS CONTROL	MIFARE IC keys (200 pcs.) User codes (200 pcs.)
PROTECTION CLASS	IP65	ADDITIONAL FUNCTIONS	Mechanical IR-cut filter
DIMENSIONS	48×133×19 mm		
INSTALLATION TYPE	Surface mount		

Unique features



Access control
Use MIFARE wireless cards or key code to unlock the door



Buttons backlight
LED button backlight in standby mode



Viewing angle
150°



Camera mode switch
Switch the camera mode between AHD and CVBS



Product page